

# Establishing ammonia emission factors for shallow pit, fully-slatted finisher buildings

## Summary

Ammonia (NH<sub>3</sub>) emissions levels determined for a fully slatted, shallow pit (<900mm) pig finisher building were determined to be significantly lower than current figures being used by the Environment Agency (EA) for permitting and permissions.

The reduction in determined emission levels are anticipated, due to a variety of factors, eg improved measuring capability and control in building environment, in addition to developments in diet formulation, genetics and modern production systems. It has been reported that 'Much of the work on which UK emissions estimates from buildings and stores are based has not reported data with enough explanatory variables to fully account for variation among reported NH<sub>3</sub> emissions' (Ricardo-AEA, 2014). 'Existing studies used in the preparation of the UK NH<sub>3</sub> inventory provide little supporting data, particularly with respect to factors such as the diet fed to the pigs, nitrogen (N) and total available N (TAN) excretion and the floor area allowed per animal' as reported by (Ricardo-AEA, 2014). Key factors not reported include growth rate and feed conversion ratio (FCR) of the pigs.

The study was conducted on a commercial farm operating to their standard practice. The study followed the Verification of Environmental Technologies for Agricultural production (VERA) Test Protocol for Livestock Housing and Management to ensure the results could be compared with other studies and were not open to the same uncertainty of past studies.

Ammonia was quantified over a year for three batches of pigs from approximately 40–120kg. This allowed us to capture emissions values during all four seasons to remove any seasonal variation. The average ammonia emission was found to be 1.72kg per animal place per year. The range recorded was 0.57 to 2.76kg. In comparison, the EA ammonia emissions factor (kg NH<sub>3</sub>/animal place/year) is currently at 3.1 for this type of system.

## Background

Ammonia is an important air pollutant that can have significant effects on both human health and ecosystems. Agriculture plays a significant role in contributing to NH<sub>3</sub> emissions and accounts for approximately 81 per cent of total ammonia emissions on an annual basis (Defra, 2018). As a consequence, reduction targets of 23 per cent by 2020 have now been put into place.

Emissions for inventory purposes (Environmental Permitting Regulation/Integrated Pollution Prevention and Control) and environmental impact modelling are calculated from a series of emissions factors that are linked to pig age and housing type. In October 2014, a report for AHDB Pork (formerly BPEX) by AEA Technology highlighted a shortcoming with the emission factors currently in use. In summary, it was concluded that 'from what the emission estimates from buildings and stores are based on, it has not reported data from enough explanatory variables to fully account for variation among reported NH<sub>3</sub> emissions'. These variables include protein levels of the feed fed (growth rate and FCR) and the floor area allowed per animal, both of which have changed dramatically over the last few years. The need for up-to-date, accurately and scientifically measured emissions factors has become all the more relevant as the European Commission published the Intensive Farming Best Available Techniques reference document (BREF), Version 2 in February 2017. This now includes emission limits associated with Best Available Techniques ammonia emission limits (BAT AELs) which must be complied with by IPPC/EPR permit holders. The aim of the study is to establish an ammonia emission factor in kilograms per animal place per year (kg/AP/yr) from a fully slatted, fully ventilated finisher building with a shallow pit (<900mm).

# Materials and Methods

## Buildings

Two modern, commercial, fully slatted, fully ventilated pig finisher buildings were used for the study. The slurry pits are emptied every 6–7 weeks.

The internal layout of the buildings is identical. Each building consists of two rows of pens (six on each side) running the length of building with a central walkway. The building is designed to house 420 pigs per room, with two rooms per building. Each pen houses approximately 35 pigs. The layout of the buildings is demonstrated in Figure 1.




Figure 1: Building and pen layout (not to scale)

The dimensions and measurements of the building are outlined in Table 1.

Table 1: Dimensions and measurements of the building

| Building feature         | Detail/measurement       |
|--------------------------|--------------------------|
| Length of building       | 19.2 metres              |
| Width of building        | 13.98 metres             |
| Height of eaves          | 2.13 metres              |
| Flooring type            | Plastic slats            |
| Depth of slurry pit      | 0.914 metres             |
| Drinkers                 | 2 (nipples)              |
| Pen size                 | 6.4 metres x 3.17 metres |
| Feeder space             | 1.6 metres per pen       |
| Feed form                | Wet feed (co-products)   |
| Building set temperature | 15-18°C                  |

Pigs enter the building at approximately 40kg and leave at approximately 120kg (roughly 92 days). The building is filled in two stages, approximately six days apart (eg one room is filled first and then the

second is filled six days later). While sampling is continuous, data has only been analysed when the building was fully stocked.

Circuit 8 building consists of 8 x 710mm fans (four in each room), with a capacity of 60,000m<sup>3</sup>/hour (per room) and 1 per cent vent of 600m<sup>3</sup>/hour. Circuit 9 Building consists of 8 x 630mm fans (four in each room), with a capacity of 40,000m<sup>3</sup>/hour (per room) and 1 per cent vent of 400m<sup>3</sup>/hour. All fans were run in two pairs in each room at variable speeds with duty fans rotating to ensure wear is evenly distributed between pairs of fans.

There are two temperature sensors in each room which are coupled to a “Dicam” controller (Farmex), which is a proportional or “P” type ventilation controller. These temperature sensors and Dicam control the ventilated rate on a room-by-room basis to maintain a stable environment.

Both buildings and ventilation systems have been built to comply with BS 5502.

The building conforms to the requirements of the Verification of Environmental Technologies for Agricultural production (VERA) Test Protocol for Livestock Housing and Management Systems. The building has been used for more than one batch of pigs. In excess of 50 pigs are housed in the weight range of 25–110kg liveweight. Growth rate in previous batches is in excess of 760g per day.

VERA states that buildings must not exceed 3000ppm of CO<sub>2</sub> (as per section 5.3). We have ensured this is the case during the monitoring periods by first using buildings built to BS 5502 (which must provide ventilation to maintain CO<sub>2</sub> concentrations below 3000ppm) and by monitoring for any abnormal ventilation events.

Stocking rates in the building meet Red Tractor standards, which are shown in Table 2.

Table 2: The minimum permitted space allowances defined by the average weight of pig

| Average Liveweight (kg) | Minimum Total Floor Area (m <sup>2</sup> /pig) |
|-------------------------|--|
| <10                     | 0.15   |
| 10.1 – 20               | 0.20   |
| 20.1 – 30               | 0.30   |
| 30.1 – 50               | 0.40   |
| 50.1 – 85               | 0.55   |
| 85.1 – 110              | 0.65   |
| >110                    | 1.00   |

## Monitoring

Ammonia concentration – Measurements of ammonia concentration were taken at the inlet and exhaust points in accordance with the Test Protocol for Livestock Housing and Management Systems (developed by VERA). The equipment used to monitor ammonia levels was a ‘Solus’ multipoint portable ammonia analyser (Protea). The Solus is based on the LGD F200 tuneable diode laser (TDL) sensor. The machine was calibrated at the beginning and end of the study and was rechecked at the end of the study and found to be accurately recording ammonia within specification. For details of the calibration, see report (Appendix 1). Ventilation systems were checked prior to the study commencing to ensure they were functioning correctly.

Air samples for analyser were taken from 10 points, with the eleventh sample acting as a purge of the optic as shown in Figure 3. Those labelled as a fan are the exhaust points and the two ambient sample points are external to the building.




Figure 3: Pen layout and numbering for ammonia analyser sampling points (not to scale)

Samples were collected throughout the study period on a continuous basis during the time the building was fully stocked.

Three production cycles (batches) were monitored in total across a 12-month period.

The analyser was located in a secure insulated box on the floor between the two buildings as shown in photo 1.



Photo 1: Area between two buildings to place ammonia analyser

## Ventilation rate

Ventilation rate and internal temperature for each room, plus external temperature, were continuously monitored and logged by an online environmental recording system (Farmex).

## Pig numbers

The number of pigs entering the building at 40kg was recorded. Pigs that were drawn early for another contract were also recorded, alongside the draw date and the average weight.

## Analysis of data

1. Average inlet and outlet ammonia gas concentration were calculated for each sampling cycle period (approximately 17 minutes).
2. The average inlet ammonia concentration was subtracted from the average outlet value to create a 'net' concentration figure.
3. The net concentration figure provides the ammonia concentration in the air leaving the building via the fan shaft (exhaust point) in ppm (attributed to the housed pigs).
4. The net concentration figure was then converted to grams of ammonia per m<sup>3</sup> of air (g/m<sup>3</sup>) using the fixed conversion figure of 0.0007\*.
5. This figure was then multiplied by the ventilation rate closest in time to the concentration readings (to provide a kg of ammonia leaving the building per hour, as ventilation rate is expressed as m<sup>3</sup>/hr), multiplied by 8760 (to provide kg ammonia per year) and then divided by the number of pigs that entered the building at the beginning of each batch recorded.
6. This figure was then multiplied by a percentage occupancy figure of 92 per cent (based on the number of days that the building is completely empty in a year) to provide a kg/ap/yr ammonia figure.

The calculation methodology was verified by Rothamsted Research.

\*The fixed figure of 0.0007 is derived from the ideal gas law that states that any gas at 1 atm pressure and 25°C occupies 24 litres. 17 (the molar mass of ammonia) is then divided by 24 to provide a conversion from PPM to grams per m<sup>3</sup> of 0.7. This was divided by 1000 to provide a conversion factor of 0.0007 from ppm to kg/m<sup>3</sup> of ammonia (assuming the building is at 1 atm at 25°C).

## Results

Table 3 shows the results of the study. In production period 3, C8 RM1 and C8 RM 2 were excluded from analysis due to veterinary intervention as a result of a health breakdown during the batch.

As per section 5.7 of the VERA protocol that states 'Measurement results during which the test location did not comply with the required management conditions (5.3)' the data from Circuit 8, rooms 1 and 2 for period 3 has been discounted as the pigs did not meet the required management conditions.

Table 3: Results from the study

| Production period | Circuit and room | Date batch started | Date batch finished | DWLG | NH <sub>3</sub> Emission Factor (kg/ap/yr) | Number of pigs |
|-------------------|------------------|--------------------|---------------------|------|--|----------------|
| 1                 | C8 RM1           | 12/04/16           | 13/07/16            | 870  | 2.71                                       | 420            |
|                   | C8 RM2           | 18/04/16           | 18/07/16            | 879  | 1.46                                       | 421            |
|                   | C9 RM1           | 14/03/16           | 08/06/16            | 930  | 1.00                                       | 420            |
|                   | C9 RM2           | 08/03/16           | 06/06/16            | 889  | 0.57                                       | 420            |
| 2                 | C8 RM1           | 19/07/16           | 26/10/16            | 808  | 2.35                                       | 422            |
|                   | C8 RM2           | 25/07/16           | 27/10/16            | 851  | 1.84                                       | 420            |
|                   | C9 RM1           | 13/06/16           | 19/09/16            | 816  | 0.97                                       | 402            |
|                   | C9 RM2           | 13/06/16           | 19/09/16            | 816  | 1.14                                       | 420            |
| 3                 | C9 RM1           | 26/09/16           | 14/12/16            | 1001 | 2.39                                       | 420            |
|                   | C9 RM2           | 26/09/16           | 13/12/16            | 1002 | 2.76                                       | 419            |
| <b>Average</b>    |                  | /                  | /                   | /    | 1.72                                       | /              |

Table 4: Pig movements during the study

| Production period | Pigs in total | Number of light pigs drawn * | Average weight of light pigs drawn | Production day at draw | Pigs remaining to bacon weight |
|-------------------|---------------|------------------------------|------------------------------------|------------------------|--------------------------------|
| 1                 | C8 RM1        | 0                            | /                                  | /                      | 420                            |
|                   | C8 RM2        | 45                           | 83.1                               | 13/06/16               | 376                            |
|                   | C9 RM1        | 43                           | 83.5                               | 09/05/16               | 377                            |
|                   | C9 RM2        | 47                           | 84.5                               | 02/05/16               | 373                            |
| 2                 | C8 RM1        | 26                           | 81.4                               | 09/09/16               | 396                            |
|                   | C8 RM2        | 26                           | 82.0                               | 09/09/16               | 394                            |
|                   | C9 RM1        | 50                           | 83.2                               | 01/08/16               | 352                            |
|                   | C9 RM2        | 26                           | 82.8                               | 08/08/16               | 394                            |
| 3                 | C9 RM1        | 33                           | 83.0                               | 14/11/16               | 393                            |
|                   | C9 RM2        | 42                           | 82.7                               | 07/11/16               | 385                            |

\*A number of pigs from each production period were sold part way through the production period (on average 83kg). The number sold varies from 0–50 across the periods. The emission factor was calculated in two sections, the first takes into account the total number of pigs housed before a selection were pulled light. The second was calculated based on the number of pigs remaining in the building till slaughter weight. This was then weighted as a percentage of time spent in each period and then corrected for annual occupancy rates per room.

The pigs were fed a combination of two diets during the finisher period. The percentage of these diets and the specification are detailed in Table 4.



Table 5: Diet specification and details

| Week number | Pig weight (kg) | Mix 1 (% fed) | Mix 2 (% fed) | TOT LYS (%) | CP (%) |
|-------------|-----------------|---------------|---------------|-------------|--------|
| Week 1      | 40              | 100           | 0             | 1.28        | 21.37  |
| Week 2      |                 | 100           | 0             | 1.28        | 21.37  |
| Week 3      |                 | 80            | 20            | 1.24        | 20.85  |
| Week 4      |                 | 70            | 30            | 1.23        | 20.59  |
| Week 5      |                 | 60            | 40            | 1.21        | 20.33  |
| Week 6      |                 | 50            | 50            | 1.19        | 20.07  |
| Week 7      | 76              | 40            | 60            | 1.17        | 19.80  |
| Week 8      |                 | 25            | 75            | 1.15        | 19.41  |
| Week 9      |                 | 15            | 85            | 1.13        | 19.15  |
| Week 10     |                 | 0             | 100           | 1.1         | 18.76  |
| Week 11     |                 | 0             | 100           | 1.1         | 18.76  |
| Week 12     |                 | 0             | 100           | 1.1         | 18.76  |
| Week 13     | 120             | 0             | 100           | 1.1         | 18.76  |

## Discussion

Table 2 shows that all three batches have an emission factor lower than current figures used by the EA. This creates an average of 1.72kg of ammonia per pig place per year (range of 0.57 to 2.76kg).

A review carried out by the Danish Ministry of the Environment in 2014 highlighted some of the factors influencing ammonia emissions include the floor type, emitting surface in the pit and the slurry depth (Danish Ministry of the Environment, 2014). Aarnink and Wagemand (1997) report that between 25 per cent and 75 per cent of the NH<sub>3</sub> emissions in a pig system originate from the slurry pit below the floor, while the rest comes from the fouled portion of the floor, thereby management can be a large influencing factor.

The study was carried out as per the VERA protocol using a calibrated a TDL gas analyser. In comparison with some of the previously published work, which was used to produce the existing emission figures, this study was based on current (2016/17) genotypes, finishing rations and production regimens. In 1995, when the emissions were originally documented, the average growth rate of pigs was significantly lower than today's production figures. However, today it is common to see an average of 841g/day (AHDB, 2018). In addition, slaughter weights have also increased from 67.2kg in 1995 to an average of approximately 82kg in 2016. As a result, the industry is producing heavier pigs over a shorter period of time. Considering this, these figures are robust and more representative of current emissions from commercial, fully slatted finisher buildings in England.

In addition to regular removal of slurry, or part slatted systems, you would expect this figure to be even lower.

## Significance and relevance to the pig industry

IPPC/EPR is a challenge for some pig businesses when they look to expand their holding. Ammonia modelling and the prediction of ammonia emissions is a key part of the IPPC/EPR process. The models are based on emissions factors that were highlighted in a 2014 report that was commissioned by BPEX (now AHDB Pork) as not reporting 'data from enough explanatory variables to fully account for variation among reported NH<sub>3</sub> emissions'.

These studies have allowed for more up-to-date and accurate figures to be scientifically determined for a variety of pig housing in the UK, using current diets, ventilation and management practices. Currently, this figure is lower than those used in the existing model by government agencies or consultants. This suggests that existing and future planned sites may be emitting less ammonia than was previously thought. This may ease the permitting process for many producers, or even alter the stocking limits on non-permitted sites.

The potential impact of this on UK pig production is considerable. These findings possibly limit the need for farmers to invest large amounts of capital in abatement technologies, which are then expensive to run on a per pig basis. As more emissions factors from other housing types are added to the study, we can more accurately compare UK-based emissions factors for these various housing types. This means that producers could potentially choose their housing type taking emissions levels into consideration. This would reduce the environmental impact of their production system and future-proof their businesses against future emissions regulations to some degree. It also allows the pig industry in the UK to actively engage with and contribute toward the industry target of a 23 per cent reduction in emissions by 2020.

In conclusion, the results from this study have been highly encouraging. A rolling programme of work is being carried out to allow for emissions factors to be accurately quantified from as many differing types of finisher and sow housing as possible, to create a database of routinely updated, scientifically established emissions factors for UK production.



## References

Aarnink, A. W. M., 1997. Ammonia volatilization and dust concentration as affected by ventilation systems in houses for fattening pigs. *Transactions of the ASAE*, 40(4), pp. 1161–1170.

Agriculture and Horticulture Development Board, 2018. *Finishing 35–110kg*. [Online] Available at: [https://pork.ahdb.org.uk/prices-stats/costings-herd-performance/finishing-35-110kg/?performanceMeasure=Daily+liveweight+gain+%28g%2Fday%29&categories\\_average=1](https://pork.ahdb.org.uk/prices-stats/costings-herd-performance/finishing-35-110kg/?performanceMeasure=Daily+liveweight+gain+%28g%2Fday%29&categories_average=1) [Accessed 18 June 2018].


Danish Ministry of the Environment, 2014. *Review of ammonia emissions from a pig house slurry pit and outside storage*. [Online] Available at: <https://www2.mst.dk/Udgiv/publications/2014/11/978-87-93283-15-2.pdf> [Accessed 10 November 2017].

Defra, 2018. *Emissions of air pollutants in the UK, 1970 to 2016*. [Online] Available at: [https://assets.publishing.service.gov.uk/government/uploads/system/uploads/attachment\\_data/file/681445/Emissions\\_of\\_air\\_pollutants\\_statistical\\_release\\_FINALv4.pdf](https://assets.publishing.service.gov.uk/government/uploads/system/uploads/attachment_data/file/681445/Emissions_of_air_pollutants_statistical_release_FINALv4.pdf) [Accessed 16 February 2018].

Ricardo-AEA, 2014. Review of ammonia and particulate emission factors from housed production of pigs and poultry DRAFT Report. Unpublished.

# Appendices

## Appendix 1. Ammonia analyser calibration information

|    |  | SERVICE SUMMARY                 |                           |          |       |
|---|--|---------------------------------|---------------------------|----------|-------|
| Customer:   | AHDB Pork  | Protea Service Contract Number: | S11046-2                  |          |       |
| Date of service:  | 19/04/2017   | Customer Purchase Order Number: | 812599                    |          |       |
| Contact name:   | Sue Rabbich  | Telephone:                      | 07772 598 412             |          |       |
| Service Carried out:  | <input checked="" type="checkbox"/> Protea <input type="checkbox"/> Site   | E-mail:                         | Susan.Rabbich@ahdb.org.uk |          |       |
| Service Engineer:   | Jake Holden  |                                 |                           |          |       |
| Analyser Model#   | SOL-T  | Analyser S/N:                   | SOL-T-1601                |          |       |
| Description of application/usage of analyser:   | Ammonia gas analyser   |                                 |                           |          |       |
| Reason for Service:   | <input checked="" type="checkbox"/> 6 monthly service <input type="checkbox"/> 12 monthly service <input type="checkbox"/> 1 off service <input type="checkbox"/> Unscheduled maintenance <input type="checkbox"/> Warranty Repair |                                 |                           |          |       |
| <b>Description of problems before work and remedial work before service</b><br>N/A  |  |                                 |                           |          |       |
| <b>Work carried out :</b>   |  |                                 |                           |          |       |
| <input checked="" type="checkbox"/>   | Confirm system details, current operation, recent issues and visual check  |                                 |                           |          |       |
| <input checked="" type="checkbox"/>   | Fault find and fix issues  |                                 |                           |          |       |
| <input checked="" type="checkbox"/>   | Carry out performance validations  |                                 |                           |          |       |
| <input checked="" type="checkbox"/>   | Gas cell service, inc. replacement of windows, o-rings, seals as appropriate   |                                 |                           |          |       |
| <input checked="" type="checkbox"/>   | Flow, temperature and pressure calibration of FTIR analyser all passed   |                                 |                           |          |       |
| <input type="checkbox"/>  | Replacement of O2 sensor (if appropriate)  |                                 |                           |          |       |
| <input checked="" type="checkbox"/>   | Re-assemble, validate and adjust analyser optics   |                                 |                           |          |       |
| <input checked="" type="checkbox"/>   | Record performance validations post-service. All passed. Instruct for future service needs on FTIR parts   |                                 |                           |          |       |
| <input checked="" type="checkbox"/>   | Sampling system equipment checks. Temperature, flow and pump checks. Alarm validations. Probe checks.  |                                 |                           |          |       |
| <input checked="" type="checkbox"/>   | Span gas validations carried out and passed  |                                 |                           |          |       |
| <input checked="" type="checkbox"/>   | Save updated calibration files   |                                 |                           |          |       |
| <b>Notes:</b>   |  |                                 |                           |          |       |
| Cleaned all the pipework inside the instrument, replaced servicable parts of the sample pump, re-calibrated the cell pressure sensor and gas cell cell. There has been quite a bit of liquid found inside of the pipework and pump, it is recommended that a knock-off pot be installed after the valves to stop the ammonia being absorbed by the liquid. The PAS-Pro software was outdated, updated to the newer 1.14.13 version. |  |                                 |                           |          |       |
| <b>Parts Used:</b>  |  |                                 |                           |          |       |
| Part Number   | Description  | Qty                             | Unit Price                | Discount | Price |
|   |  |                                 |                           |          | £ -   |
|   |  |                                 |                           |          | £ -   |
|   |  |                                 |                           |          | £ -   |
|   |  |                                 |                           |          | £ -   |
|   |  |                                 |                           |          | £ -   |
|   |  |                                 |                           |          | £ -   |
|   |  |                                 |                           |          | £ -   |
| <b>PARTS SUB TOTAL</b>  |  |                                 |                           |          | £ -   |
| Labour Charge (normal hours)  | _____ hours @ £  | _____                           | 75 /hour                  | £        | -     |
| Mileage Charges   | _____ miles @ £  | _____                           | 0.45 /mile                | £        | -     |
|   | Other Travel Costs   |                                 |                           |          |       |
|   | Subsistence  |                                 |                           |          |       |
|   | TOTAL  |                                 |                           | £        | -     |
| Full service tasks check sheet and diagnostic results sheet available on request  |  |                                 |                           |          |       |
| Signed for Protea Limited:  |  | Signed (Customer):              |                           |          |       |

PROTEA LIMITED  
 10 Prosperity Court  
 Middlewich, Cheshire UK  
 CW10 0GD

Form PL 47/4

Span Check

Analyser: SOL-T-1601 Date: 19/04/2017

Gas cylinder number:   
 Certificate number: 40006443275



| Component | Certified Concentration | Stable readings | Average | Difference / Conc. | Difference / % |
|-----------|-------------------------|-----------------|---------|--------------------|----------------|
| NH3       | 9.7                     | 9.24            | 9.24    | 0.5                | 4.7            |

While the Agriculture and Horticulture Development Board seeks to ensure that the information contained within this document is accurate at the time of printing, no warranty is given in respect thereof and, to the maximum extent permitted by law, the Agriculture and Horticulture Development Board accepts no liability for loss, damage or injury howsoever caused (including that caused by negligence) or suffered directly or indirectly in relation to information and opinions contained in or omitted from this document.

Reference herein to trade names and proprietary products without stating that they are protected does not imply that they may be regarded as unprotected and thus free for general use. No endorsement of named products is intended, nor is any criticism implied of other alternative but unnamed products.

© Agriculture and Horticulture Development Board 2018.  
All rights reserved

